

In the Claims:

Please amend the claims as follows:

Claims 1-15 (Canceled).

16. (Currently Amended) A copier system comprising:

a copier capable of being monitored by a personal computer from a remote location, the copier comprising a control computer controlling the performance of the copier, and a control panel configured to receive data from the control computer;

a chip corresponding to the copier, the chip providing an interface for connecting the copier with a bi-directional network, said bi-directional network being capable of connecting the personal computer to a plurality of devices, and

a memory device corresponding to the copier, the memory device storing data comprising a special information to identify the copier in the network, the memory device capable of retaining data if power to the memory device is removed,

wherein said chip transmits the special information ~~when transmitted~~ to the personal computer and identifies the copier remotely in the network and enables recognition of the copier by a database manager of the personal computer.

17. (Currently Amended) The copier system according to claim 16, wherein the chip converts ~~has first circuitry for converting~~ serial data transmitted from the personal computer into parallel data and converts ~~converting~~ parallel data transmitted from the copier into serial data, ~~and second circuitry for driving a pair of signal lines according to the converted serial data, the first and second circuitry being incorporated in the chip.~~

18. (Previously Presented) The copier system according to claim 16, further comprising the network wherein the network comprises a plurality of lines, each of the plurality of lines having at least a pair of signal lines transmitting asynchronous serial data.
19. (Currently Amended) The copier system according to claim 18, wherein the plurality of lines comprise four signal lines having ~~comprising~~ the pair of signal lines.
20. (Previously Presented) The copier system according to claim 19, wherein the pair of signal lines comprise a hard wiring.
21. (Previously Presented) The copier system according to claim 18, wherein the pair of signal lines has high immunity from external noise sources.
22. (Previously Presented) The copier system according to claim 18, wherein the control computer is mounted on a computer board.
23. (Cancelled).
24. (Cancelled).
25. (Currently Amended) The copier system according to claim 18, wherein the chip is ~~comprises~~ a microprocessor.
26. (Currently Amended) The copier system according to claim 25, wherein the microprocessor is connected to ~~comprises~~ an address decoder.
27. (Previously Presented) The copier system according to claims 18, further comprising the personal computer, wherein a condition of the copier and setup parameters, a copy count and error codes of the copier are displayed on a display screen of the personal computer.
28. (Previously Presented) The copier system according to claims 18, wherein the control panel comprises a light emitting diode.

29. (Previously Presented) The copier system according to claims 18, wherein the control panel comprises a liquid crystal display.

30. (Previously Presented) The copier system according to claim 18, wherein the control panel comprises a plurality of keys.

31. (Previously Presented) The copier system according to claim 18, wherein an error status signal is sent from the control computer to the control panel.

32. (Currently Amended) A copier system capable of being monitored and controlled by a remote computer, the copier system ~~image-forming device~~ comprising:

a copier machine;

a computer controller housed in ~~coupled to~~ the copier machine and configured to generate ~~monitor~~ a status of the copier machine; and

an interface for connecting the copier system ~~image-forming device~~ with the remote computer by a bi-directional communication line connected to the remote computer, the interface comprising:

a ~~chip comprising~~ a microprocessor;

a ~~nonvolatile~~ memory storing a special information and being capable of retaining the special information if power to the copier system is removed;

a ~~parallel-to-serial converter~~ circuit for converting a first parallel data stream from the microprocessor into a first serial data stream[[]] and a ~~serial-to-parallel converter~~ ~~circuit~~ for converting a second serial data stream from the remote computer into a second parallel data stream which the microprocessor processes[[]]; and

a driver circuit capable of transmitting the first serial data stream over the bi-directional communication line,

wherein the special information identifies the copier and enables recognition of the copier by a database manager operating on the remote ~~personal~~ computer.

33. (Currently Amended) The copier system according to claim 32, wherein the microprocessor is connected to ~~comprises~~ an address decoder.

34. (Currently Amended) The copier system according to claim 32, wherein the remote computer is ~~comprises~~ a personal computer.

35. (Currently Amended) The copier system according to claim 32, wherein the status of the copier machine monitored by the remote computer ~~controller~~ comprises at least one of setup parameters, a copy count and error codes of the copier, and wherein data representing at least one of the setup parameters, copy count and error codes of the copier are transmitted via the interface to the remote computer in a format enabling a representation of the data to be displayed on a display screen of the remote ~~personal~~ computer.

36. (New) A copier system comprising:

a copier capable of being monitored by a personal computer from a remote location, the personal computer being connected to the copier system via a network, the network comprising a pair of wires to bi-directionally transmit serial data;

a memory corresponding to the copier, the memory storing a special information to identify the copier and enables recognition of the copier by a database manager operating on the personal computer, the memory capable of retaining data if power to the memory is removed;
and

a universal asynchronous receiver/transmitter for transmitting the special information to the personal computer through the network, the universal asynchronous receiver/transmitter converting parallel data used by said copier into serial data to be placed on the pair of wires.

37. (New) The copier system according to claim 36, wherein a status of the copier monitored by the personal computer comprises at least one of setup parameters, a copy count and error codes of the copier, and wherein data representing at least one of the setup parameters, copy count and error codes of the copier are transmitted via the universal asynchronous receiver/transmitter to the personal computer to be displayed on a display screen of the personal computer.